

電漿(等離子)清洗機

c sun

Plasma



特色：

- 適用大批量生產 (High Throughput) >2400片/hr
- 系統穩定度高MTBF>500hrs
- High COO value
- 多家太陽能電池公司採用，獲製程品質的肯定

Leading in Thermal and UV Light Processing Equipment

Specifications\Type	PRS-CH
Material of chamber	Aluminum alloy whit surface treatment
Inner Chamber	Ø380mmxH305mm
Application	1. Edge isolation(去邊蝕刻) of solar cell 2. Texture(表面粗化) of solar cell
Plasma source	ICP model (Inductively Coupled Plasma)
Power source	RF Generator,13.56MHz,1000W
Standard gas	O ₂
Gas flow control	Analog type MFC
Standard pump	Dry pump(>150m ³ /hr)
Base pressure	>10 ⁻² Torr
Process pressure	50~200mTorr (depending on parameters of process)
Automatic system	15" TFT panel / IPC / Windows 2000 XP
Dimension	(W)1200mm x (D)1150mm x (H)2050mm

Due to C SUN continuing efforts to improve their systems, these specifications are subject to change without notice.
受長期研發需要，本公司保有規格修改之權利，恕不另行通知

DM201606-0000

業務洽詢專線： +86-139-22532580 (華南) +86-138-62666327 (華東) +886-922-225015 (臺灣)

andyhuang@csun.com.tw

台北

新北市林口區工二工業區
工八路2-1號
TEL:886-2-26017706
FAX:886-2-26018854

台中

台中市南屯區
精科二路11號
TEL:886-4-23591651
FAX:886-4-23592678

廣州

廣州市花都區獅嶺鎮
利和路6號
TEL:86-20-86846341-3
FAX:86-20-86910139

東莞

東莞市大朗鎮長塘第三工業區78號
松湖雲谷雲松樓1樓
TEL:86-769-85331146
FAX:86-769-85331145

昆山

江蘇省昆山市高新區(玉山鎮)
恒盛路1369號
TEL:86-512-57780230
FAX:86-512-57780229