



機台特點 Characteristics

- 特殊腔內壓力穩定設計
Special bore pressure and stable design
- 加壓氣體可自由選用CDA / N2
Pressurized gas can be free to use the CDA / N2
- 溫度及壓力採PID控制
Temperature and pressure PID control
- 水冷式降溫系統設計
Of water-cooled cooling system design
- 機台壓力與溫度狀況即時顯示 / 監控
Machine pressure & temperature status of real-time display / monitor
- 壓力及溫度採整頁式設定，簡易又清楚
Pressure and temperature to adopt a full-page settings, simple and clear



www.csun.com.tw

內尺寸 Interior (mm)	W440 × D400 × H400mm × 2爐	W440 × D400 × H400mm × 2 Furnace
外尺寸 Exterior (mm)	W1400 × D1650 × H1970 + 250mm	W1400 × D1650 × H1970 + 250mm
電源 Power	AC220 / 380V 50 / 60HZ 19KVA × 2爐	AC220 / 380V 50 / 60HZ 19KVA × 2 Furnace
溫度範圍 Temp. Range	+60°C~200°C	+60°C~200°C
溫度控制 Temp. Controller	自動PID控制、電子感應、數字顯示	Digital Display and Automatic PID Control±0.5%
溫度系統 Control System	輸入：K Type感應棒 輸出：SSR無接點繼電器	Input：K Type Sensor Output：SSR
溫度均勻度 Temp Uniformity	150°C ± 3°C (空載)	at 150°C ± 3°C (Non-load)
昇溫速率 Heating rate	平均升溫速率 >6°C/mins (空載)	The Average Heating Rate >6°C/mins (Non-load)
降溫時間 Cooling time	150°C → 60°C <18分鐘 (空載)	150°C → 60°C <18mins (Non-load)
壓力系統 Pressure Systems	可程式壓力控制，Max: 10kg/cm ²	Programmable Pressure Control Max: 10kg/cm ²
進氣口 Inlet	Air Ø1/2" ; N2 Ø1/2"	Air Ø1/2" ; N2 Ø1/2"
排氣口 Outlet	Ø3/4"	Ø3/4"
材質 Materials	內部SUS304#不鏽鋼板 外部SS41#鋼板粉體烤漆	Interior：Stainless Steel Exterior：Steel with Baked Enamel Rockwool Insulation
電熱 Heater	特製圓弧式無塵化電熱器	Arc Clean of Electric Heaters
安全裝置 Safety Device	漏電斷路器 超溫防止保護裝置 機台異常蜂鳴器警示 電熱過電流保護裝置 三相逆向防止器 馬達過電流保護裝置 控制線路保險絲裝置 超壓防止保護裝置 控制按鍵加防觸蓋	Leakage Circuit Breaker Over Temperature Protection Buzzer Protection Devices for Heater Overload Three-phase Reverse to Prevent Motor Overcurrent Protection Device The Control Circuit Fuse Device Overpressure to Prevent the Protection Device Control Buttons Plus Anti-touch Cover
標準配件 Standard Parts	壓力計 電磁門扣 圓孔盤 門面安全開關 專利循環風扇系統	Differential Pressure Gauge Electromagnetic Door Lock SUS304# Perforated Tray Patent Circulating Fan System
選購品 Option	溫度記錄器 六點溫度顯示器 三色指示燈	Programmable Temp. Controller Six-point Temperature Display Tri-color Indicator

Due to C SUN continuing efforts to improve their systems, these specifications are subject to change without notice.
受長期研發需要，本公司保有規格修改之權利，恕不另行通知

DM202103-500-TW

+86-159-6252-1975 (華東)

+86-136-0029-3510 (華南)

+886958-925529 (臺灣)

super.lu@csun.com.tw

台北

新北市林口區工二工業區
工八路2-1號
TEL:886-2-26017706
FAX:886-2-26018854

台中

台中市南屯區
精科二路11號
TEL:886-4-23591651
FAX:886-4-23592678

廣州

廣州市花都區獅嶺鎮
利和路6號
TEL:86-20-86846341-3
FAX:86-20-86910139

東莞

東莞市大朗鎮長塘第三工業區78號
松湖雲谷雲松樓1樓
TEL:86-769-85331146
FAX:86-769-85331145

昆山

江蘇省昆山市高新區(玉山鎮)
恒盛路1369號
TEL:86-512-57780230
FAX:86-512-57780229