



機台特點 Characteristics

- 平坦化能力：錫條 $9 \times 9 = 81$ 點驗證， 610×610 mm 全域範圍內可達 20 um 以下
(at 0.7 MPa at 610×610 mm)
Flatness: < 20um by 610mm x 610mm area. Testing point: 81 points by tin stick. Pressure: 0.7MPa
- 最大加壓面壓力可達1.15MP at 610×610 mm (1.65MP at 510×510 mm)
Pressure : The maximum pressure can be up to 1.15MP at 610×610 mm (1.65MP at 510×510 mm)
- PET具黏塵及靜電消除功能
PET Cleanliness : PET films can be eliminated static electricity and be cleaned by Web cleaner.
- 入料段採離位設計，提供容易裝換PET膜便利性。
Convenience : Extendable unwinding module creates a convenient operating space to change and setup the PET films easily.

PL-A24

機板尺寸 Panel Dimension	寬度：250~610mm 長度：250~610mm 厚度：0.05 ~ 3 mm (不含銅;單邊銅厚>=1/3oz)	Width : 250~610mm Length : 250~610mm Thickness : 0.05 ~ 3 mm (Without copper ; Single thickness>=1/3oz)
壓膜製程 Lamination Process	輸送速度：1~10M/min (可調) 加壓壓力： MAX 1.15Mpa (Panel size 610 × 610mm) 加熱器：18 KW × 2	Conveyor Speed : 1~10M/min (Adjustable) Pressure : MAX 1.15Mpa (Panel size 610 × 610mm) Heater : 18 KW × 2
機台尺寸/重量 External Dimension/ Weight	L2400 × W2400 × H2250 (mm) 含油壓單元空間 / 8300 kg L2400 × W1770 × H2250 (mm) 本體 / 8000 kg + L1250*W800*H1100油壓系統/300kg	L2400 × W2400 × H2250 (mm) Including hydraulic system / 8300 kg L2400 × W1770 × H2250 (mm) Machine / 8000 kg + L1250*W800*H1100 Hydraulic system /300kg
公共需求 Utilities	電力：AC220V 3φ 60HZ 53 KVA 139 A 氣壓：5~7 kgf/cm ²	Power : AC220V 3φ 60HZ 53 KVA 139A Compressed Air : 5~7 kgf/cm ²
溫度控制 Temperature Controller	PID方式 + S.S.R.驅動	PID Control + S.S.R. Driving
控制方式 Operation Control	可程式控制器 + 觸控式螢幕	PLC + Touch Screen Monochrome LCD Display
排氣 Exhaust	φ4" × 2 : 10 CMM	φ4" × 2 : 10 CMM

Due to C SUN continuing efforts to improve their systems, these specifications are subject to change without notice.
 受長期研發需要，本公司保有規格修改之權利，恕不另行通知

DM201801-50KS